





linear dimension(Tolerances Standard GB/T 14486-2008)



variable range	to 6	over 6	over 10	over 30	over 60	over 100	over 160	to 10	over 10	over 100
		to 10	to 30	to 60	to 100	to 160	to 100		to 100	
tolerance	±0.20	±0.30	±0.50	±0.70	±1.00	±1.30	±1.60	0.10	0.30	0.60

REVISION RECORD				
REV.	DESCRIPTION	ECN No.	APPROVED	DATE

UL/CUL 技术参数 UL/CUL Technical Data						
等级 Use Group	B	C	D			
额定电压 Rated Voltage [V]	300	-	300			
额定电流 Rated Current [A]	10	-	10			
接线范围 Wire Range				22-14		
单/多芯线 Solid/Stranded [AWG]						
耐电压 Withstanding Voltage				1600V/1Min		
IEC 技术参数 IEC Technical Data						
过电压类别 Overvoltage Category	III	III	II			
污染等级 Contamination Class	3	2	2			
额定电压 Rated Voltage [V]	250	400	500			
额定电流 Rated Current [A]	17	17	17			
额定冲击电压 Impulse withstand voltagea [KV]	4.0	4.0	4.0			
导线截面积 Conductor cross section				1.5		
硬质/柔性导线 Solid/flexible [mm²]						
材料 Material						
绝缘材料 Insulation Material				PA66		
阻燃等级 Imflammability				UL94V-0		
导体材料 Contactor Material				铜合金 Copper alloy		
导体表面镀层 Contactive Coating				镀镍 Ni Plated		
一般参数 Other Data						
间距 Pitch [mm]				5.0		
极数 Poles [P]				2-24		
剥线长度 Stripping Length [mm]				4-5		
螺丝 Screw/扭矩 Torque(Max) [N.m]				M2.5/0.4		
工作温度 Operating temperatur [°C]				-40~105		
引针尺寸 Pin Dimensions [mm]				-		
PCB板孔径 PCB Hole Diameter [mm]				-		



DES.	DATE	单位 / UNITS	mm	尺寸 / SIZE	A4	比例 / SCALE	1:1	第三视角/THIRD ANGLE PROJECTION	版本 / REV	A
CHK.	DATE	慈溪市科发电子有限公司 CIXI KEFA ELECTRONIC CO., LTD							名称 / TITLE KF331W-5.0	
APP.	DATE									